





| SYSTEM DESCRIPTION            |                                             | FIRE STOPPING INFORMATION |                      | SERVICE SIZE & DETAILS                                                                                                                                                                                                                              | SUPPORTING INFORMATION  |  |                |         |
|-------------------------------|---------------------------------------------|---------------------------|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|--|----------------|---------|
| Orientation:                  | Wall                                        | BOSS Batt™                | BOSS FireMastic-300™ | Up to 65 mm uPVC DWV pipe with 2.7 mm maximum wall thickness, penetrating 2 layers of BOSS Batt™ protecting an aperture up to 1200 mm x 500 mm. Sealant 5 mm deep in 7.5 mm annular gap both sides. 80 mm BOSS MaxiCollar™ installed on both sides. | Reference Standard:     |  | AS 1530.4:2014 |         |
| Trade / Type:                 | Plumbing / Hydraulic / Active Fire          | BOSS Ablative Coating™    | -                    |                                                                                                                                                                                                                                                     | Supplementary Standard: |  | AS 4072.1-2005 |         |
| Service:                      | UPVC                                        | BOSS MaxiCollar™          | -                    |                                                                                                                                                                                                                                                     | Report Reference:       |  | WF FAS 210203  |         |
| Substrate:                    | Single Layer Fire Rated Plasterboard System | APERTURE (mm)             | ANNULAR GAP (mm)     |                                                                                                                                                                                                                                                     | Drawing Number:         |  | BF-2969.1      |         |
| Min Substrate Thickness (mm): | 90.0                                        | Up to 1200 x 500          | 7.5                  |                                                                                                                                                                                                                                                     | Date:                   |  | 20/08/25       | Rev: 01 |
| Sealant Depth (mm):           | 5.0                                         | ADDITIONAL INFORMATION    |                      |                                                                                                                                                                                                                                                     |                         |  |                |         |
| Sealant Fillet (mm):          | -                                           |                           |                      |                                                                                                                                                                                                                                                     |                         |  |                |         |
| Wrap Length (mm):             | -                                           |                           |                      |                                                                                                                                                                                                                                                     |                         |  |                |         |
| FRL / FRR:                    | -/60/60                                     |                           |                      |                                                                                                                                                                                                                                                     |                         |  |                |         |