





| SYSTEM DESCRIPTION            |                                          | FIRE STOPPING INFORMATION |                  | SERVICE SIZE & DETAILS                                                | SUPPORTING INFORMATION  |  |                |      |
|-------------------------------|------------------------------------------|---------------------------|------------------|-----------------------------------------------------------------------|-------------------------|--|----------------|------|
| Orientation:                  | Wall                                     | BOSS PenoPatch™ 60mm      | -                | 20 mm blank aperture protected by BOSS PenoPatch™ 60mm on both sides. | Reference Standard:     |  | AS 1530.4:2014 |      |
| Trade / Type:                 | Construction (Linear Gaps / Blank Seals) | BOSS FireMastic-300™      | -                |                                                                       | Supplementary Standard: |  | AS 4072.1-2005 |      |
| Service:                      | -                                        | -                         | -                |                                                                       | Report Reference:       |  | FAS190100 R2.1 |      |
| Substrate:                    | Masonry                                  | APERTURE (mm)             | ANNULAR GAP (mm) |                                                                       | Drawing Number:         |  | BF-3420.5      |      |
| Min Substrate Thickness (mm): | 118                                      | 20                        | -                |                                                                       | Date:                   |  | 06/11/25       | Rev: |
| Sealant Depth (mm):           | -                                        | ADDITIONAL INFORMATION    |                  |                                                                       |                         |  |                | 01   |
| Sealant Fillet (mm):          | -                                        |                           |                  |                                                                       |                         |  |                |      |
| Wrap Length (mm):             | -                                        |                           |                  |                                                                       |                         |  |                |      |
| FRL / FRR:                    | -/120/60                                 |                           |                  |                                                                       |                         |  |                |      |

IMPORTANT: This drawing is provided as a guide only and does not guarantee compliance for every application. Confirm that the supporting certification is applicable to your specific construction details and obtain acceptance from the relevant Certifying Authority before installation. BOSS Passive Fire reserves the right to amend this document without notice.